

Estimate for: Construction of Public Toilet at Dinbazar Muri Patty in Ward No- 4 nder Jalpaiguri Municipality[ULB Model]. Model - F

Sl.No	Description of Item							Quantity	Rte	Unit	Amount	
	Location	N	N	L	W/B	H/D	Total					
1	Earth work in excavation of foundation trenches or drains, in all sorts of soil (including mixed soil but excluding laterite or sandstone) including removing, spreading or stacking the spoils within a lead of 75 m. as directed. The item includes necessary trimming the sides of trenches, levelling, dressing and ramming the bottom, bailing out water as required complete. (a) Depth of excavation not exceeding 1,500 mm. [PWD BUILDING WORKS, Page- 1, It. No- 2.a]							13.82	11927.00	%Cum	1648.31	
	Column	6.00	1.00	1.20	1.20	1.13	9.72					
	Tie Beam	2.00	1.00	5.50	0.45	0.43	2.1					
		3.00	1.00	1.25	0.45	0.43	0.72					
	Part beam	4.00	1.00	1.50	0.45	0.43	1.15					
	Stair	1.00	1.00	2.35	0.75	0.08	0.13					
							13.82					
2	Earth work in filling in foundation trenches or plinth with good earth, in layers not exceeding 150 mm. including watering and ramming etc. layer by layer complete. (Payment to be made on the basis of measurement of finished quantity of work) (a) With earth obtained from excavation of foundation [PWD BUILDING WORKS, Page- 1, It. No- 3.a]							9.26	7754.00	%Cum	718.02	
	2/3 of It. No- 1											
							0.67	13.82				
3	4 (A) Filling in foundation or plinth by silver sand in layers not exceeding 150 mm as directed and consolidating the same by thorough saturation with water, ramming complete including the cost of supply of sand. (payment to be made on measurement of finished quantity) [PWD BUILDING WORKS, Page- 2, It. No- 4.a]							5.06	52107.00	%Cum	2636.61	
	Toilet, urinal											
							1.00	1.00	1.50	5.63	0.60	5.06
							5.06					
4	Single Brick Flat Soling of picked jhama bricks including ramming and dressing bed to proper level and filling joints with local sand. [PWD BUILDING WORKS, Page- 14, It. No- 1]							29.08	324.00	Sq.M.	9421.92	
	Column	6.00	1.00	1.20	1.20		8.64					
	Tie Beam	2.00	1.00	6.25	0.45		5.63					
		3.00	1.00	1.75	0.45		2.36					
	Part Beam	4.00	1.00	1.25	0.45		2.25					
	Stair	1.00	1.00	2.35	0.75		1.76					
	Floor	1.00	1.00	5.63	1.50		8.44					
							29.08					
5	(II) Cement concrete with 30 mm down graded shingles excluding shuttering. N.B. Variety In ground floor (a) 1:3:6 proportion [PWD BUILDING WORKS, Page- 35, It. No- 22,II, a)]											
	Column	6.00	1.00	1.20	1.20	0.10	0.86					
	Tie Beam	2.00	1.00	6.25	0.45	0.10	0.56					
		3.00	1.00	1.75	0.45	0.10	0.24					
	Part Beam	4.00	1.00	1.00	0.45	0.10	0.18					
	Partation wall	2.00	1.00	6.25	0.25	0.60	1.88					
		3.00	1.00	1.75	0.25	0.60	0.79					
		4.00	1.00	1.25	0.25	0.60	0.75					
	Stair	1.00	1.00	2.35	0.75	0.15	0.26					
		1.00	1.00	2.35	0.50	0.15	0.18					
		1.00	1.00	2.35	0.25	0.15	0.09					
	Floor	1.00	1.00	5.63	1.50	0.10	0.84					

		1.00	1.00	5.63	1.50	0.10	0.84			
							6.63	3260.93	Cu.M	21619.97
Primary Cement concrete (mix 1:1.5:3) with graded stone chips (20 mm nominal size) excluding shuttering and reinforcement if any. in ground floor as per relevant IS codes. (i) Pakur Variety [PWD BUILDING WORKS. Page- 26. It. No- 10. i]							6.63	3260.93	Cu.M	21619.97
Footing		6.00	1.00	1.20	1.20	0.20	1.73			
(1.20 + 0.40) 2 = 0.80		6.00	1.00	0.80	0.80	0.20	0.77			
		6.00	1.00	0.40	0.40	0.30	0.29			
Tie Beam		2.00	1.00	6.25	0.25	0.25	0.78			
Tie Beam		3.00	1.00	1.75	0.25	0.25	0.33			
Part beam		4.00	1.00	1.25	0.25	0.25	0.31			
Co[3.0+(0.6-0.25)]= 3.3		6.00	1.00	0.25	0.25	3.35	1.26			
Lintel		2.00	1.00	5.50	0.25	0.20	0.55			
		3.00	1.00	1.25	0.25	0.20	0.19			
Protection wall		4.00	1.00	1.25	0.13	0.20	0.13			
Chazza		4.00	1.00	0.50	0.45	0.10	0.09			
Roof beam		2.00	1.00	6.25	0.25	0.13	0.39			
		3.00	1.00	1.75	0.25	0.13	0.16			
Roof slab		1.00	1.00	6.25	1.75	0.13	1.37			
							8.35	₹ 5,871.07	Cu.M	49023.43
7	25mm. thick damp proof course with cement concrete with stone chips (1:1.5:3) [with graded stone aggregate 10 mm nominal size] and admixture of water proofing compound as per manufacturer's specification followed by two coat of polymer based paint. (1st coat after 4 to 5 days of concrete laying and 2 nd coat just before brick masonry work) as directed (cost of water proofing compound & polymer based paint to be paid separately).(Chequering not required over concrete or painted surface). [Note: - Waterproofing as per item 9. polymer based paint as per item 8 (a) of subhead C of Section (C). [PWD BUILDING WORKS. Page- 47. It. No- 1]						8.35	₹ 5,871.07	Cu.M	49023.43
	Tie Beam	2.00	1.00	6.25	0.25		3.13			
		3.00	1.00	1.75	0.25		1.31			
	Part beam	4.00	1.00	1.25	0.13		0.63			
							5.07	318.33		1613.93
							5.07	496.00	Sq.M.	993.72
8	125 mm. thick brick work with 1st class bricks in cement mortar (1:4) in ground floor. [PWD BUILDING WORKS. Page- 16. It. No- 16]						5.07	496.00	Sq.M.	993.72
	Partation wall [3.0-(.2+.125)= 2.675]	4.00	1.00	1.25		2.68	13.38			
	Parapet wall	1.00	1.00	16.00		0.30	4.8			
							18.18	666.37		12,114.61
							18.18	487.92	Sq.M.	8870.4
9	Supplying and laying Polythene Sheet (150gm / sq.m.) over damp proof course or below flooring or roof terracing or in foundation or in foundation trenches.or. [PWD BUILDING WORKS. Page- 47. It. No- 3]						8.44	24.00	Sq.M.	202.56
		1.00	1.00	5.63	1.50		8.44			
10	Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor) (When the height of a particular floor is more than 4 m the equivalent floor height shall be taken as 4 m and extra for works beyond the initial 4 m ht. shall be allowed under 12 (e) for every 4 m or part thereof) (f) 25 mm to 30 mm shuttering without staging in foundation [PWD BUILDING WORKS. Page- 37. It. No- 36. f]						8.44	24.00	Sq.M.	202.56
	Footing	6.00	4.00	1.20		0.20	5.76			

	6.00	4.00	0.40		0.30	2.88
	6.00	4.00	0.25		0.60	3.60
Beam	2.00	2.00	6.25		0.25	6.25
	3.00	2.00	1.75		0.25	2.63
Part beam	4.00	2.00	1.25		0.25	2.50
						23.62

23.62 205.00 ✓ Sq.M. 4842.10

11 Hire and labour charges for shuttering with centering and necessary staging upto 4 m using approved stout props and thick hard wood planks of approved thickness with required bracing for concrete slabs, beams and columns, lintels curved or straight including fitting, fixing and striking out after completion of works (upto roof of ground floor)
(When the height of a particular floor is more than 4 m the equivalent floor height shall be taken as 4 m and extra for works beyond the initial 4 m ht. shall be allowed under 12 (e) for every 4 m or part thereof)
(a) 25 mm to 30 mm thick wooden shuttering as per decision & direction of Engineer-In-Charge.
[PWD BUILDING WORKS, Page- 36, It. No- 36. a]

Column	6.00	4.00	0.25		2.75	16.50
Lintel	2.00	2.00	5.50		0.20	4.40
	3.00	2.00	1.50		0.20	1.80
Partitaion wall	4.00	2.00	1.25		0.20	2.00
Openning. Door	2.00	1.00	1.05		0.25	0.53
	2.00	1.00	0.75		0.13	0.19
Window	4.00	1.00	0.45		0.25	0.45
Chazza	4.00	1.00	0.50		0.45	0.90
	4.00	1.00	1.40		0.10	0.56
Roof beam	2.00	1.00	6.25		0.13	1.56
	3.00	1.00	1.75		0.13	0.66
Outerside	1.00	1.00	16.00		0.25	4.00
Roof slab	1.00	1.00	6.25	1.75		10.94
						44.49

44.49 328.00 ✓ Sq.M. 14592.72

12 Artificial stone in floor, dado, staircase etc with cement concrete (1:2:4) with stone chips, laid in panels as directed with topping made with ordinary or white cement (as necessary) and marble dust in proportion (1:2) including smooth finishing and rounding off corners including raking out joints or roughening of concrete surface and application of cement slurry before flooring works using cement @ 1.75 kg/sq.m all complete including all materials and labour.
In ground floor.
3 mm. thick topping (High polishing grinding on this item is not permitted with ordinary cement).
Using grey cement
(ii) 25 mm. thick
[PWD BUILDING WORKS, Page- 42, It. No- 6. ii]

Roof	1.00	1.00	6.25		1.75	10.94
------	------	------	------	--	------	-------

10.94 262.37 ✓ Sq.M 2870.33

13 Reinforcement for reinforced concrete work in all sorts of structures including distribution bars, stirrups, binders etc initial straightening and removal of loose rust (if necessary), cutting to requisite length, hooking and bending to correct shape, placing in proper position and binding with 16 gauge black annealed wire at every intersection, complete as per drawing and direction
(a) For works in foundation and upto roof of ground floor/upto 4 m
(i) Tor steel/Mild Steel
II. JSW/JSPL/SHYAM/ SRMB/BMASL/ELECROSTEEL/SSL
[PWD BUILDING WORKS, Page- 43, It. No- 40. a.i]

1.20% of Item No(6)	0.01	8.35	7.85			0.787
---------------------	------	------	------	--	--	-------

0.787 58537.78 ✓ MT 46069.23

gate with 40mm x 40mm x 6mm Tee as top and bottom guide rail.
 10mm x 2mm vertical channels 100mm apart in fully stretched position
 X 5mm M.S. flats as collapsible bracings properly rivetted and washed
 including 38mm steel rollers including locking arrangements, fitted and fixed in
 position with lugs set in cement concrete and including cutting necessary holes,
 chasing etc. in walls, floors etc. and making good damages complete.
 (Add extra @ 1% for each addl. floor upto 4th floor and @ 1.25% for each addl.
 floor above 4th floor)
 In ground floor.
 [PWD BUILDING WORKS, Page- 106, It. No- 18]

	2.35		1.00	2.10		4.94	4.94	4351.00	Sq.M	21493.94
								3773.00		-18638.62

15 Brick work with 1st class bricks in cement mortar (1:4)
 (b) In superstructure, ground floor
 [PWD BUILDING WORKS, Page- 15, It. No- 7. b]

[3.0-(.25+.2) = 2.55]	1.00	2.00	5.50	0.25	2.55	7.01				
	1.00	3.00	1.25	0.25	2.55	2.39				
Deduction										
Window	-4.00	1.00	0.45	0.25	0.60	-0.27				
Door	-2.00	1.00	1.05	0.25	2.10	-1.10				
						8.03	8.03	5324.56	Cu.M	42.756 ²²

16 Labour for Chipping of concrete surface before taking up Plastering work.
 [PWD BUILDING WORKS, Page- 192, It. No- 1]

Column	6.00	4.00	0.25		3.35	20.10				
Lintel	2.00	2.00	5.50		0.20	4.40				
	3.00	2.00	1.25		0.20	1.50				
Partition wall	4.00	2.00	1.25		0.20	2.00				
Below opening										
Window	4.00	1.00	0.45		0.25	0.45				
Door	2.00	1.00	1.05		0.25	0.53				
	2.00	1.00	0.75		0.13	0.19				
Chazza	4.00	1.00	1.40		0.10	0.56				
Roof beam	2.00	1.00	6.25		0.25	3.13				
	3.00	1.00	1.75		0.25	1.31				
In side	2.00	2.00	6.25		0.13	3.13				
Inside	2.00	1.00	1.75		0.13	0.44				
Roof	1.00	1.00	6.25		1.75	10.94				
						48.68	48.68	21.000	Sq.M	1022.28

17 Plaster (to wall, floor, ceiling etc.) with sand and cement mortar including
 rounding off or chamfering corners as directed and raking out joints including
 throating, nosing and drip course, scaffolding/staging where necessary (Ground
 floor).[Excluding cost of chipping over concrete surface]
 (i) With 1:6 cement mortar
 (c) 15 mm thick plaster
 [PWD BUILDING WORKS, Page- 189, It. No- 1.]

Outside	1.00	2.00	6.25		3.90	48.75				
	1.00	3.00	1.75		3.90	20.48				
Chazza	4.00	1.00	0.45	0.50		0.9				
	4.00	1.00	1.40		0.10	0.56				
Inside	2.00	1.00	5.50		3.90	42.9				
	4.00	1.00	1.50		3.90	23.4				
Partion wall	4.00	1.00	1.25		2.88	14.38				
Parapet wall	1.00	2.00	6.25	0.13		1.56				
	1.00	2.00	1.75	0.13		0.44				
Insde	1.00	2.00	6.25		0.30	3.75				
	1.00	2.00	1.75		0.30	1.05				
Deduction	-2.00	1.00	2.35		2.10	-9.87				
	-2.00	2.00	0.75		2.10	-6.30				

	ed Section.	4.00	1.00	0.60			2.40	2.40	658.00 ✓	Mtr.	1579.2
	eat angle (Non-annodized).	4.00	4.00	0.45			7.20	7.20	263.00 ✓	Mtr.	1893.6
<p>about charge for fabrication and installation of composite door, window, partitions made from annodized extruded alloy aluminium sections for the following units:-</p> <p>(A) Glazed aluminium sliding windows made of extruded and annodized alloy aluminium sections, fabrications, including cutting to proper shape and size, drilling and aligning of window shutter frame fitted with in built locking arrangements, sliding rollers and other necessary fittings, fixture, adhesives and joineries along with extruded neoprene or EPDM gasketing in between window frame and masonry work (walls, column, beam,lintels etc.) as well as between glass and shutter frame for fixing glass and Polysulphide sealant and in between shutter and window frame where necessary including cutting to requisite size and fixing glass as per drawing, specification and direction of EIC.</p> <p>The rate includes the hire charge of all tools and plants, including all incidental charges, adhesive, joineries such as screw, cleat angle etc. but excluding the cost of extruded aluminium sections, glass, neoprene / EPDM gasket, locking arrangement and rollers.</p> <p>v) Louvered window [PWD BUILDING WORKS. Page- 240. It. No- 2. A.v]</p>											
		4.00	1.00	0.45		0.60	1.08	1.08	730.00	Sq. M	788.4
32	Supplying bubble free float glass of approved make and brand conforming to IS: 2835-1987. iv) 5mm thick coloured / tinted / smoke glass. [PWD BUILDING WORKS. Page- 243. It. No- 9.iv]							1.08	585.00 ✓	Sq. M	631.8
33	a) M.S.or W.I. Ornamental grill of approved design joints continuously welded with M.S. W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. (i) Grill weighing above 10 Kg./sq.mtr and up to 16 Kg./sq. mtr. [PWD BUILDING WORKS. Page- 104, It. No- 13. a i]							0.475	9827.00 ✓	Qntl	4667.83
	Pump house	6.00	1.00	0.60		0.60	2.16				
	Window	4.00	1.00	0.45		0.60	1.08				
							3.24				
				2.97	16.00	47.52	0.475				
34	Rendering the Surface of walls and ceiling with White Cement base WATER PROOF wall putty of approved make & brand.(1.5 mm thick) [PWD BUILDING WORKS. Page- 198. It. No- 5]							99.48	122.00 ✓	Sq. M	12136.56
	same as- It. No- (17+18)-(19+29)		139.84	11.84	9.60	42.60	99.48				
35	Applying Interior grade Acrylic Primer of approved quality and brand on plastered or concrete surface old or new surface to receive Distemper/ Acrylic emulsion paint including scraping and preparing the surface thoroughly, complete as per manufacturer's specification and as per direction of the EIC. (In Ground Floor) (b) Two Coats i) Water based interior grade Acrylic Primer [PWD BUILDING WORKS. Page- 196. It. No- 7.b.i]							29.95	4420.00 ✓	%Sq.M	1323.79
	Insdie	4.00	1.00	2.33		0.78	7.21				
	3.0-(.125+2.1)= 0.78	2.00	1.00	4.35		0.78	6.74				
		2.00	1.00	1.60		0.78	2.48				
		2.00	1.00	1.20		0.78	1.86				
		2.00	1.00	1.00		0.78	1.55				
	Slab	1.00	1.00	4.35		2.33	10.11				
							29.95				
36	Dry Distemparing to interior walls or ceiling including cleaning, washing, smoothening surface (b) Two coat [PWD BUILDING WORKS. Page- 196. It. No- 7.b.i]							29.95	49.00 ✓	Sq. M	1467.55

<p>Exterior grade Acrylic primer of approved quality and brand on or concrete surface old or new surface to receive decorative textured (finish) or smooth finish acrylic exterior emulsion paint including scraping and preparing the surface throughly, complete as per manufacturer's specification and as per direction of the EIC.</p> <p>In Ground Floor: (b) Two Coats [PWD BUILDING WORKS, Page- 196, It. No- 9..b]</p>														
Outer side		1.00	2.00	6.25		3.60	45							
		1.00	2.00	1.75		3.60	12.6							
Chazza		4.00	2.00	0.45		0.50	1.8							
		4.00	1.00	1.40		0.10	0.56							
Parapet wall		1.00	2.00	6.25		0.13	1.56							
		1.00	2.00	1.75		0.13	0.44							
In side		1.00	2.00	6.25		0.30	3.75							
		1.00	2.00	1.75		0.30	1.05							
Deduction		-4.00	1.00	0.45		0.50	-0.9							
		-2.00	1.05	1.05		2.10	-4.63							
							61.23							
						61.23	4510.00 ✓	%Sq.M	2761.47					
38	Protective and Decorative Acrylic exterior emulsion paint of approved quality, as per manufacturer's specification and as per direction of Engineer-in-Charge to be applied over acrylic primer as required. The rate includes cost of material, labour, scaffolding and all incidental charges but excluding the cost of primer. In Ground floor (Two Coat) a) Normal Acrylic Emulsion [PWD BUILDING WORKS, Page- 197, It. No- 17.a]													
						61.23	67.00 ✓	Sq.M	4102.41					
39	(b) Priming one coat on timber or plastered surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. [PWD BUILDING WORKS, Page- 200, It. No- 1. b]													
						9.21	38.00 ✓	Sq. M	349.98					
40	(a) Priming one coat on steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. [PWD BUILDING WORKS, Page- 200, It. No- 1. a]													
Pump house		6.00	1.00	0.60		0.60	2.16							
Window		4.00	1.00	4.50		0.50	9.00							
Collapsible		1.00	2.00	2.35		2.10	9.87							
							21.03							
						21.03	29.00 ✓	Sq. M	609.87					
41	(A) Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary : (a) On timber or plastered surface : With super gloss (hi-gloss) - (iv) Two coats (with any shade except white) [PWD BUILDING WORKS, Page- 200, It. No- 2. a.iv]													
						9.21	81.00 ✓	Sq. M	746.01					
42	(A) Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary : (b) On steel or other metal surface : With super gloss (hi-gloss) - (iv) Two coats (with any shade except white) [PWD BUILDING WORKS, Page- 201, It. No- 2. b.iv]													
						21.03	79.00 ✓	Sq. M	1661.37					
43	Painting block letters or digits in Black Japan or any approved paint as per direction. e) Size above 7.5 cm. and upto 10 cm. [PWD BUILDING WORKS, Page- 268, It. No- 17. e]													
						450.00	12.00 ✓	Sq. M	5400.00					

	and Planting of different plant / trees (Supplying well grown plants and healthy, minimum height as specified i.e. exposed height including all lift, carriage, handling, manuring, applying pesticide and fertilizer etc.				
	v) Furcaria variegated 10-12 leaves in height 20-30cm in earthen pots of size 25cm. [PWD BUILDING WORKS, Page- 261, It. No- 9. i]	7.00	162.00 ✓	Each	1134.00
45.B	x) Ficus blakii (F. Vivicon) well branched (Bushy) of height 120cm - 135 cm in earthen pot of size 30cm. [PWD BUILDING WORKS, Page- 261, It. No- 9. x]	3.00	187.00 ✓	Each	561.00
45.C	xxvi) Areca Palm 4 - 5 suckers of height 90 cm to 105 cm in earthen pots of size 25 cm. [PWD BUILDING WORKS, Page- 262, It. No- 9. xxvi]	3.00	127.00 ✓	Each	381.00




SANITARY AND PLUMBING WORKS


46	Supplying, fitting and fixing Anglo-Indian W.C. in white glazed vitreous china ware of approved make complete in position with necessary bolts, nuts etc. (a) With 'P' trap (with vent) [SANITARY AND DRAINAGE WORKS, Page- 79, It. No- 3. a]	2.00	3104.00 ✓	Each	6208.00
47	Supplying, fitting and fixing Closet seat of approved make with lid and C.P. hinges, rubber buffer and brass screws complete. (b) Anglo Indian (i) Plastic (hallow type) black [SANITARY AND DRAINAGE WORKS, Page- 81, It. No- 10. b.i]	2.00	371.00 ✓	Each	742.00
48	Supplying, fitting and fixing Flat back urinal (half stall urinal) in white vitreous chinaware of approved make in position with brass screws on 75 mm X 75 mm X 75 mm wooden blocks complete. (ii) 470 mm X 280 mm X 340 mm [SANITARY AND DRAINAGE WORKS, Page- 80, It. No- 6. ii]	2.00	945.00 ✓	Each	1890.00
47	Supplying, fitting and fixing Squating plate with integral flushing in white vitreous chinaware of approved make in cement concrete (6:3:1) with jhama chips complete. (Payment of concrete will be paid separately). (i) 450 mm X 350 mm [SANITARY AND DRAINAGE WORKS, Page- 80, It. No- 7. i]	1.00	881.00 ✓	Each	881.00
48	Supplying, fitting and fixing 10 litre P.V.C. low-down cistern conforming to I.S. specification with P.V.C. fittings complete, C.I. brackets including two coats of painting to bracket etc. [SANITARY AND DRAINAGE WORKS, Page- 36, It. No- 2]	2.00	1015.00 ✓	Each	2030.00
49	Supplying, fitting and fixing 32 mm dia. Flush Pipe of approved make with necessary fixing materials and clamps complete. i) Polythene Flush Pipe [SANITARY AND DRAINAGE WORKS, Page- 81, It. No-11.i]	2.00	155.00 ✓	Each	310.00
50	Supplying, fitting and fixing urinal flush pipe fittings of approved brand. (a) C.P. urinal flush pipe fittings range of one [SANITARY AND DRAINAGE WORKS, Page- 81, It. No-12.a]	3.00	414.00 ✓	Each	1242.00
51	Supplying, fitting and fixing white vitreous china best quality approved make wash basin with C.I. brackets on 75 mm X 75 mm wooden blocks, C.P. waste fittings of 32 mm dia., one approved quality brass C.P. pillar cock of 15 mm dia., C.P. chain with rubber plug of 30 mm dia., approved quality P.V.C. waste pipe with C.P. nut 32 mm dia., 900 mm long approved quality P.V.C. connection pipe with heavy brass C.P. nut including mending good all damages and painting the brackets with two coats of approved paint. (ii) 550 mm X 400 mm size [SANITARY AND DRAINAGE WORKS, Page- 41, It. No-2.ii]	2.00	2208.00 ✓	Each	4416.00
52	Supplying, fitting and fixing pedestal of approved make for wash basin (white) [SANITARY AND DRAINAGE WORKS, Page- 41, It. No-3]	2.00	1497.00 ✓	Each	2994.00
53	Supplying, fitting and fixing approved brand P.V.C. CONNECTOR white flexible, with both ends coupling with heavy brass C.P. nut, 15 mm dia. (iii) 600 mm long [SANITARY AND DRAINAGE WORKS, Page- 43, It. No- 9.iii]	5.00	107.00 ✓	Each	535.00

	fitting and fixing approved brand 32 mm dia.P.V.C. waste pipe, with coupling at one end fitted with necessary clamps. 1050 mm long [SANITARY AND DRAINAGE WORKS, Page- 43, It. No- 10.iv]	4.00	91.00 ✓	Each	364.00
	(f) Hand Shower(Health Faucet) with 1mtr Flexible Tube with Wall Hook(Equivalent to Code No.573 & Model -ALLIED of Jaquar or similar). [SANITARY AND DRAINAGE WORKS, Page- 3, It. No- 3.f]	2.00	1251.00 ✓	Each	2502.00
56	(a) (i) Chromium plated Bib Cock short body (Equivalent to Code No. 511 & Model - Tropical / Sumthing Special of ESSCO or similar brand). [SANITARY AND DRAINAGE WORKS, Page- 6, It. No- 7. a.i]	3.00	539.00 ✓	Each	1617.00
57	(b) (i) Chromium plated Stop Cock (Equivalent to Code No. 513(A) & 513(B) & Model - Tropical / Sumthing Special of ESSCO or similar [SANITARY AND DRAINAGE WORKS, Page- 6, It. No- 7. b.i]	1.00	493.00 ✓	Each	493.00
58	(d) (i) Chromium plated angular Stop Cock with wall flange (Equivalent to Code No. 5053 & Model - Florentine of Jaquar or similar brand). [SANITARY AND DRAINAGE WORKS, Page- 6, It. No- 7. d.i]	5.00	815.00 ✓	Each	4075.00
59	a) (i) CP Pillar Cock - 15 mm. (Equivalent to Code No. 507 & Model - Tropical / Sumthing Special of ESSCO or similar brand). [SANITARY AND DRAINAGE WORKS, Page- 45, It. No- 19. a.i]	2.00	555.00 ✓	Each	1110.00
60	Supplying, fitting and fixing PVC pipes of approved make of Schedule 80 (medium duty) conforming to ASTM D - 1785 and threaded to match with GI Pipes as per IS : 1239 (Part - I), with all necessary accessories, specials viz. socket, bend, tee, union, cross, elbo, nipple, long screw, reducing socket, reducing tee, short piece etc. fitted with holder bats clamps, including cutting pipes, making threads, fitting, fixing etc. complete in all respect including cost of all necessary fittings as required, jointing materials and two coats of painting with approved paint in any position above ground. (Payment will be made on the centre line measurements of total pipe line including all specials. No separate payment will be made for accessories, specials. Payment for painting will be made seperately) (a) For Exposed Work. PVC Pipes, 25 mm [SANITARY AND DRAINAGE WORKS, Page- 12, It. No- 19. i.a]	15.00	177.00 ✓	Mtr.	2655.00
60	(a) For Exposed Work. PVC Pipes, 15 mm [SANITARY AND DRAINAGE WORKS, Page- 12, It. No- 19. i.a]	10.00	101.00 ✓	Mtr.	1010.00
61	Supplying, fitting and fixing gunmetal wheel valve of approved brand and make tested to 21 kg per sq. cm. (for water lines only). (vii) 25 mm dia [SANITARY AND DRAINAGE WORKS, Page- 5, It. No- 5. vii]	2.00	778.00 ✓	Each	1556.00
62	Supplying P.V.C. water storage tank of approved quality with closed top with lid (Black) - Multilayer (b) 1000 litre capacity [SANITARY AND DRAINAGE WORKS, Page- 37, It. No- 6. b]	2.00	5128.00 ✓	Each	10256.00
63	Labour for hoisting plastic water storage tank. (i) Upto 1500 litre capacity. [SANITARY AND DRAINAGE WORKS, Page- 37, It. No- 10. i]	2.00	96.00 ✓	Each	192.00
64	Labour for punching hole in plastic water storage tank upto 50 mm dia. [SANITARY AND DRAINAGE WORKS, Page- 38, It. No- 13]	2.00	19.00 ✓	Each	38.00
65	Labour for punching hole in plastic water storage tank upto 50 mm dia. [SANITARY AND DRAINAGE WORKS, Page- 37, It. No- 10. i]	2.00	19.00 ✓	Each	38.00
66	Supply of UPVC pipes (B Type) & fittings conforming to IS-13592- 1992.(A) (i) Single Socketed 3 Meter Length, (b) 110 mm PWD S&P Schedule. Page No.-68 Item No. 23,(A)(i)(b)	30.00	292.00 ✓	Mtr	8760.00
67	(B) Fittings (i) Coupler. (b) 110 mm	8.00	85.00 ✓	Each	680.00

		12.00	85.00 ✓	Each	1020.00
		10.00	195.00 ✓	Each	1950.00
		10.00	89.00 ✓	Each	890.00
		7.00	147.00 ✓	Each	1029.00
		30.00	21.00 ✓	Each	630.00
	W.C. connector (150 mm long) 125 X 110 W.C. Ring 75 mm	4.00	142.00 ✓	Each	568.00
	Plan Floor Trap with Top tile & Strainer 75 mm	7.00	144.00 ✓	Each	1008.00
	Rubber Ring (b) 110 mm	15.00	17.00 ✓	Each	255.00
	Rubber Lubricant 500 ML	1.00	187.00 ✓	500 ML	187.00
	DD Solvent Cement 250 ML	1.00	103.00 ✓	250 ML	103.00
78	Labour for fitting and fixing U.P.V.C. pipes for above ground work including cost of jointing materials etc. fitting and fixing all necessary specials, cutting pipes, cutting holes in total pipeline including specials. (B) Under ground. (ii) 110 mm dia PWD S&P Schedule. (P - 74, Item. No. - 24 (B))	20.00	84.00 ✓	Mtr	1680.00
79	Supplying, fitting & fixing UPVC pipes A- Type and fittings conforming to IS 13592-1992 with all necessary clamps nails, including making holes in walls, floor etc. cutting trenches in any soil through masonry concrete structures etc if necessary and mending good damages including joining with jointing materials (Spun Yarn, Valamoid Bitumen/M-Seal etc) complete. A) UPVC Pipes (i) 75 mm. Dia. (P - 212, Item. No. - 21 (A)(i), (B).(c).(i) & (B), (d).(i). PwD volume- i, 2017)	20.00	188.00 ✓	Mtr	3760.00
80	B) UPVC Fittings: c) Bend 87.5 degree (i) 75 mm. Dia.	6.00	84.00 ✓	Mtr	504.00
81	B) UPVC Fittings: d) Shoe (i) 75 mm. Dia.	2.00	78.00 ✓	Mtr	156.00
82	Constructing Inspection pit of inside measurement 600mm X 600mm X upto 600mm (depth) with 250 mm thick 1st. class brick work in cement mortar (1:4) on all sides, bottom of the pit consisting of 100 mm thick cement concrete (1:3:6) with stone chips over a layer of jhama brick flat soling, 15 mm thick (1:4) cement plaster to inside walls and out-side walls upto G.L. and 20 mm.thick (1:4) plaster to bottom of the pit, providing necessary invert with cement concrete (1:3:6) with stone chips as per direction, neat cement finishing to entire internal surfaces, top of the pit covered with 100 mm thick R.C.C. slab (1:1.5:3) with stone chips and necessary reinforcements upto 1% and shuttering including 6 mm thick cement plaster (1:4) in all external surfaces of the slab and one 560 mm dia. R.C.C. manhole cover of approved make supplied, fitted and fixed in the slab with necessary fittings, necessary earthwork in excavation in all sorts of soil, filling sides of the pit with earth and removing spoils after work complete in all respect with all costs of labour and materials. i) With Pakur variety (Other than SAIL/TATA/RINL). PWD S&P Schedule, S.P.87,Item No-1(i), 7th Corrigenda Volume ii	2.00	7248.00 6450.00	Each	14496.00 12900.00


	<p>Construction of septic tank of different capacities as per approved drawing with brick work in cement mortar (1:4) including two 560 mm dia. R.C.C. manhole cover (heavy type) of approved make supplied, fitted and fixed in the 100 mm thick R.C.C (1:1.5:3) top slab with necessary fittings, 20mm thick cement plaster (4 : 1) with neat cement finish to the internal surfaces and 15 mm thick cement plaster (4 : 1) to outside wall upto 200 mm below G.I. floor finished with 25 mm thick grey artificial stone over 100 mm thick R.C.C(1:1.5:3) bottom slab including supplying, fitting and fixing all necessary specials, fittings, S.W. tees, C.I. foot rest etc. including excavation earth in all sorts of soil, shoring, bailing out and pumping out water as necessary, ramming, dressing the bed and refilling the sides of the tanks with earth, removing spoils, filling up the chamber with clear water, removing foreign materials from the chamber and including constructing attached inspection pit as per approved drawing and connecting all necessary pipes, joints etc. with internal plaster work and artificial stone flooring is to be done with admixture of water proofing compound @ 0.5% by weight of cement with all costs of labour and materials.</p> <p>(ii) For 20 users</p> <p>A) With Pakur variety. (JSW/JSPL/SHYAM/SRMB/ELECTROSTEEL/SSL) PWD S&P Schedule. S.P.88.Item No-3(ii)(A) 7th Corrigenda Volume ii</p>	1.00	44519.00 48162.00	Each	44519.00 48162.00
84	<p>Construction of circular soak well 2.5 metre deep in all types of sandy soils with dry brick work upto 1.6 metre from the bottom having 150 mm intermediate cement brick work (1:4) band all round and cement brick work (1:4) upto 0.90 metre from top with 20mm thick cement plastering (1:4) to inside face upto the depth of cement brick work. 15mm thick cement plaster (1:4) on outer face from top of the well upto G.L. and 6 mm thick cement plaster (1:4) on top of the R.C.C. cover slab including filling bottom 1.00 metre of inside of the well with brick metal (50 mm to 63 mm size) including R.C.C. cover slab of 100 mm thick with cement conc (1:1.5:3) with stone chips with necessary reinforcement and shuttering including one 560 mm dia. R.C.C. manhole cover (heavy type) of approved make supplied, fitted and fixed in the cover slab with necessary fittings, making necessary arrangements for pipe connections, excavation of well including shoring, dewatering and removing the excess earth from the premises as per direction complete in all respect with all costs of labour and materials. With 250 mm thick dry brick work and 250 mm thick cement brick work (1:6) and 1.00m inside dia.</p> <p>(Other than SAIL/TATA/RINL) S.P.89.Item No-4 7th Corrigenda Volume ii</p>	1.00	15554.00 16621.00	Each	15554.00 16621.00
85	<p>Supplying, fitting and fixing towel rail with two brackets.</p> <p>(a) C.P. over brass</p> <p>(ii) 25 mm dia. and 600 mm long</p> <p>PWD S&P Schedule. p No 82 I No- 22 (a)(ii)</p>	2.00	430.00	Each	860.00
86	<p>Supplying, fitting and fixing bevelled edged mirror 5.5 mm thick silver red as per I.S. 3438 / 1965 together with brass C.P. hinges. (ii) 600 mm X 450 mm</p> <p>PWD S&P Schedule. P-81, It-15(ii)</p>	2.00	484.00	Each	968.00
87	<p>Supplying, fitting and fixing soap holder.</p> <p>(b) Fibre glass</p> <p>Sanitary and plumbing work schedule P-82, It-18(b)</p>	2.00	58.00	Each	406.00
88	<p>Supplying, fitting and fixing glass shelf with aluminium guard rails.</p> <p>(a) Ordinary type with 5.5 mm sheet glass</p> <p>(i) 450 mm X 125 mm</p> <p>Sanitary and plumbing work schedule P-81, It-16(a)(i)</p>	2.00	341.00	Each	682.00
			5,03,456.43	Total Amount excluding GST	500731.6
			45,311.08	Add CGST @ 9%	45065.84
			45,311.08	Add SGST @ 9%	45065.84
			5,94,078.59	Total amount including GST	590863.28
			5,940.79	Add Labour Welfare Cess. @ 1%	5908.63
			6,00,019.38	Total Amount Including L.abour Welfare Cess.	596771.91
			17,822.36	Add Contingency @3%	17725.9
			6,17,841.74	Total Amount Including L.W.C. and contingency	614497.81
			6,17,842.00	Say Rupees	614498.00

 Junior Engineer
 Jalpaiguri Division M.E. Dte.
 Assistant Engineer
 Jalpaiguri Division M.E. Dte.
 Executive Officer
 Jalpaiguri Municipality

 Executive Engineer
 Jalpaiguri Division M.E. Dte.




FRONT VIEW




SEC. E-E FOR COL. C2
SCALE - 1:25


SEC. E-E FOR COL.
SCALE - 1:25




SECTION F-F
SCALE - N.T.S.




R.C. DET. OF BEAM CURTAILMENT
SCALE - N.T.S.




CROSS SECTIONAL VIEW AT X-Y



PLAN OF RCC FOUNDATION (1:25)



SITE PLAN



CROSS SECTION OF RCC FOUNDATION (1:25)

DRAWING FOR THE PROPOSED COMMUNITY TOILET AT
DINBAZAR MURI PATTY IN WARD NO 04 UNDER J.M.



	Description of Item	Quantity	Rte	Unit	Amount
	Schedule Item Sl. No. 91-106 (Order as per SUDA) standard plastic dustbin (4 nos)	4.00	350.00	Each	1400.00
	Binage APC based & Reflective vinyl	5.00	3776.00	each	18880.00
	Supplying and fixing sinage with fixing stand post for public toilet for visible to passersby	5.00	1000.00	Each	5000.00
4	Glow Sign board Name and contact details of the following are displayed prominently - Toilet Identification number , name of ULB under which jurisdiction toilet is coverwd , ward number and maintainance authority prominently displayed for each toilet block supervisor, supervisor's agency and area sanitary inspector.	1.00	5000.00	each	5000.00
		1.00	2071.00	each	2071.00
5	Installation of Sinage	5.00	216.00	Each	1080.00
6	Air freshner(pack of 4nos)	5.00	210.00	Each	1050.00
7	Air freshner (Napthaline 250 gm)	5.00	50.00	Each	250.00
8	Supplying paper Napkin	4.00	520.00	Each	2080.00
9	Supplying Sanitary Napkin (Whisper or similar make 50 pcs)	4.00	300.00	Each	1200.00
10	Harpic (blue 500 ml)	4.00	150.00	Each	600.00
11	Harpic (Red 500 ml)	4.00	350.00	Each	1400.00
12	Gala double lip floor wiper	2.00	200.00	Lit	400.00
13	Colin glass or surface cleaner	2.00	145.00	Lit	290.00
14	Muriatic Acid	4.00	120.00	Kg	480.00
15	Bleaching powder	6.00	140.00	Lit	840.00
16	Dettol ,lifeboey or similar make liquid soa	4.00	80.00	Pair	320.00
17	Rubber hand gloves	6.00	125.00	Each	750.00
18	Double side plastic brush	4.00	170.00	Each	680.00
19	Plastic Broom				
20	SMS any other ICT based feedback system (With number displayed on which SMS has to be sent)	1.00	5000.00	each	5000.00
21	Mini Tulu Pump	1.00	4000.00	each	4000.00
22	supplying roaster register for keeping acoount of regular cleanig	3.00	200.00	Each	600.00
23	Lettering on Toilet Wall for display of name and contact details of ULB ward number and name of maintainance authority , saniinspector, etc.	1.00	1000.00	each	1000.00
				Total Amount-	54371.00
				Add 1% Labor welfare cess-	543.71
				Amount including Labor welfare cess-	54914.71
				Add 3% Contingency	1631.13
				Amount including Contingency	56545.84
				Say Rupees	56546.00

Rs 39,267.00


Rs. 392.67


Rs 30,659.67


Rs 1172.01

Rs 40,821.68

Rs 40,233.00



Junior Engineer
Jalpaiguri Division M.E. Dte.


Sub-Assistant Eng.
Jalpaiguri Municipality


Assistant Engineer
Jalpaiguri Division M.E. Dte.


Saikat Chatterjee
Vice- Chairman
Jalpaiguri Municipality


Executive Officer
Jalpaiguri Municipality


30/04/25
Executive Engineer
Jalpaiguri Division M.E. Dte